## PRODUCT B

# **Gerber Static Cling**

| DESCRIPTION            | 1 |
|------------------------|---|
| INTENDED APPLICATIONS  | 1 |
| APPLICATION TECHNIQUES | 1 |
| PRINTING               | 2 |
| PROTECTING GRAPHICS    | 2 |
| CUTTING                | 2 |
| SHELF LIFE AND STORAGE | 3 |
| MAINTENANCE            | 3 |
| PHYSICAL PROPERTIES    | 3 |
| RELATED LITERATURE     | 3 |
| CONTACT INFORMATION    | 3 |



#### **CUTTING**

Gerber Static Cling can be cut on any 15-inch EDGE-compatible sprocketed plotter. A 30° SuperSharp blade is recommended. Plotters can be set to full speed. A test cut should be performed by the user to determine the proper tool force setting.

### SHELF LIFE AND STORAGE

Gerber Static Cling can be stored for three months after purchase. Film should be kept in a clean area free from excessive moisture and direct sunlight. Maintain temperature at less than 75°F (23°C) and ensure 75% relative humidity.

Use a paper interleaf between printed materials that are stacked or rolled. Do not store printed graphics face to face.

#### **MAINTENANCE**

To clean printed graphics, use a mild, non-abrasive soap with a soft cloth or sponge. Avoid using alcohol-based cleansers or soaps containing grit or abrasives

#### PHYSICAL PROPERTIES

| Thickness                | 7 mils       |
|--------------------------|--------------|
| Film Color               | Clear, White |
| Adhesive                 | n/a          |
| Adhesive Color           | n/a          |
| Minimum Application Temp | 40 F (5 C)   |

#### RELATED LITERATURE

Refer to Product Bulletins of relevant foils and materials for product-specific handling, production, and finishing information.

#### **CONTACT INFORMATION**

For help with questions concerning Gerber products, please call your distributor or Gerber Customer Service at 1-800-222-7446 or (860) 644-1551. Visit us on the Internet at <a href="https://www.gerbertechnology.com/signage">www.gerbertechnology.com/signage</a> to learn more about our many other foils, materials and equipment.

When sold by Gerber, use only the corresponding Gerber Product Bulletin to determine product details, including but not limited to appropriate uses, warranty and processing.

EDGE, GERBER EDGE, GERBER EDGE 2, Gerber Scientific Products, GerberCal, GerberGraphics, GRAPHIX ADVANTAGE, GSP, and Images on Vinyl are Registered Trademarks of Gerber Technology.

Abrasion Guard, ColorSet, EDGE Positive, EDGE READY, Gerber AutoMag, GERBER EDGE FX, Gerber FastFacts, Gerber Guard, Gerber HoloGraphix, Gerber ImageCal, Gerber ImageCast, Gerber InstaChange, Gerber OMEGA, Gerber PermaGrip, Gerber PlastiGraphix, Gerber QUANTUM, Gerber StrikeGuard, Gerber Tone, Gerber UVGuard, GerberColor, GerberColor, GerberColor, GerberGauge, GerberGlow, GerberMag, GerberMask, GerberVision, GS 15, GS15plus, GSP Plot, GSxplus, GSx,