



**I** <sup>TM</sup> **2125 Banner Frontlit**

**agePefect**

**DESCRIPTION**

ImagePerfect 2125 Banner, Frontlit material from Gerber is a flexible and soft top-quality premium coated banner with excellent thermal welding characteristics and printability. This product has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks, as well as latex inks (including 3rd generation).

IP 2125 offers a high print quality with remarkable text definition and a large color gamut to ensure colorful images and vibrant area infills. It is UV-stabilized and incorporates an anti-fungus treatment making it perfect for indoor and outdoor applications such as billboards at trade shows and events, construction sites, show rooms, promotional campaigns and many other applications.

**SPECIFICATIONS**

Property	Description
Film	Cast-coated frontlit banner
Film Color	Satin White
Thickness	18.5 mil
Weight	15 oz/yd <sup>2</sup>
Tensile Strength	(2200 / 1900 N/5cm) 251.24 lb/in – 216.98 lb/in
Tear Resistance	(300 / 250 N ) 67.44 lbf – 56.20 lbf
Temperature Range	-4°F to 158 °F (-20°C to +70°C)
Durability (Unprinted)	5 years
Shelf Life	1 year
Flame Retarding	B1 (German DIN 4102 B1)
Recommendation	For optimum quality, please ensure that the media feed adjustment has been completed for this material

Note: Technical Specifications are subject to change without prior notice. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

**CONTACT INFORMATION**

For help with questions concerning Gerber products, please call your distributor or Gerber Customer Service at 1-800-222-7446 or (860) 644-1551. Visit us on the Internet at



