

# Gerber LexEdge™ Clear

DESCRIPTION.....	1
INTENDED APPLICATIONS .....	1
PRINTING .....	1
CUTTING .....	2
SHELF LIFE AND STORAGE .....	2
MAINTENANCE &.....	3
PHYSICAL PROPERTIES.....	3
CHEMICAL RESISTANCE (UNPRINTED) .....	3



Since LexEdge Clear will often be used in second-surface applications, reverse-print procedures will need to be followed. LexEdge Clear is shipped with the print surface rolled out. When printing on LexEdge Clear, a specific color of foil will often be used as a solid backing color. This color will generally be assigned as an overprint. In order to ensure that this color covers the other printed graphics as completely as possible, it may be necessary to alter its print settings. (This will be especially needed when the backing foil will be printed on top of more than two other colors.)

V@Á:ã ó^cã \*•Á:Á@Áæã \*Á:ã&ã Á^Á&ã \*^ãÁ Á@Á~ æ Ú[[ ó&^^} ÉÖ[ Á ç Á@Á:ã ó U:ã^!+Á&^^} ÁÖFFDã áÁ^!&ÁÜOVVÖ ÖÜÉÖ|æ Á} ÁÖÖÜS+Á Á@Á ç^!:] :ã ó æ^Á} |^ È

GerberColor Spot (GCS), GerberColor Process Pro CMYK (GCP), and GerberColor Transparent (GCT) Series Foils can be used to print onto LexEdge Clear. LexEdge Clear palettes and print settings are available in GRAPHIX ADVANTAGE® 6.21 Service Pack 1 and higher for the Gerber EDGE



shows up as a surface haze or clouding, stress cracking of formed parts, complete ink delamination or -in the advanced stages- de-polymerization of the polycarbonate. ***Pink Poly should not be used in close proximity to any polycarbonate product including hard***



## CONTACT INFORMATION

For help with questions concerning Gerber products, please call your distributor or Gerber Customer Service at 1-800-222-7446 or (860) 644-1551. Visit us on the Internet at [www.gerbertechnology.com/signage](http://www.gerbertechnology.com/signage) to learn more about our many other foils, materials and equipment.

When sold by Gerber, use only the corresponding Gerber Product Bulletin to determine product details, including but not limited to appropriate uses, warranty and processing.

EDGE, GERBER EDGE, GERBER EDGE 2, Gerber Scientific Products, GerberCal, GerberGraphics, GRAPHIX ADVANTAGE, GSP, and Images on Vinyl are Registered Trademarks of Gerber Technology.

Abrasion Guard, ColorSet, EDGE Positive, EDGE READY, Gerber AutoMag, GERBER EDGE FX, Gerber FastFacts, Gerber Guard, Gerber HoloGraphix, Gerber ImageCal, Gerber ImageCast, Gerber InstaChange, Gerber OMEGA, Gerber PermaGrip, Gerber PlastiGraphix, Gerber QUANTUM, Gerber StrikeGuard, Gerber Tone, Gerber UVGuard, GerberCal, GerberColor, GerberColor Spectratone, GerberGauge, GerberGlow, GerberMag, GerberMask, GerberVision, GS 15, GS15plus, GSP Plot, GSxplus, GSx, ImagePerfect, IMAGE READY, LexEdge, Matched Technology System, MTS, OMEGA, Process Pro, SpectraShade, and SpectraTint are Trademarks of Gerber Technology.

LEXAN is a Registered Trademark of General Electric Company.

3M is a trademark of 3M Company.

©2018 Gerber Technology. All Right Reserved

**Category:** EDGE READY

**FastFact #:**5504

**Supplied by:** Aftermarkets

**Last Modified:** 02/27/18

